



# Fleet

**AUG. BOLTEN**  
Wm. Miller's Nachfolger

## Diana Bolten



<b>Name:</b>	Diana Bolten
<b>Built:</b>	2011
<b>Flag:</b>	Liberia
<b>Class:</b>	NKK
<b>Type:</b>	Craned double-hull single-deck bulk carrier, boxshaped
<b>Dwat:</b>	38,273 mts on 10.536 m ssw 37,209 mts on 10.317 m wsw
<b>Tpc:</b>	48.77 mts on summer draft
<b>L.o.a.:</b>	179.97 m
<b>Beam:</b>	29.80 m
<b>Moulded depth:</b>	15.00 m

### Distance waterline to top of hatch coaming in light ballasted condition:

midships about 11.90 m

<b>Tonnage:</b>	(International):	gt/nt	23,264 / 12,134
<b>Hatches:</b>	5		
<b>Hatch sizes:</b>	No. 1	15.86 m x 17.16 m	
	No. 2	20.04 m x 20.02 m	
	No. 3	20.04 m x 20.02 m	
	No. 4	20.04 m x 20.02 m	
	No. 5	20.04 m x 20.02 m	

### Type of hatchcovers:

Foldable hydraulic hatch covers

Hold:	Sizes:	Length	Breadth (fore/aft)	Height	Grain / Bale (cub.m)
	<b>No 1:</b>	27.55 m	7.60 m / 22.70 m	13.60 m	7,707.42 / 7,380.07
	<b>No 2:</b>	27.55 m	25.80 m	13.60 m	9,932.74 / 9,575.67
	<b>No 3:</b>	27.55 m	25.80 m	13.60 m	9,966.81 / 9,578.52
	<b>No 4:</b>	27.55 m	25.80 m	13.60 m	9,955.17 / 9,581.28
	<b>No 5:</b>	27.55 m	25.80 m / 9.10 m	13.60 m	9,563.50 / 9,256.93

### Total capacity in cubic meters:

**47,125.65 / 45,372.45**

<b>Gear:</b>	4 x 30.5 mts cranes
<b>Tanktop strength:</b>	Hold 1, 3 and 5: 20.00 mts/sqm; hold 2 and 4: 15 mts/sqm
<b>Ventilation:</b>	Natural
<b>Speed/consumption:</b>	About 14.0 kn on about 25.0 mts IFO 380 cst, all incl. A/E, no MGO at sea About 12.25 kn on about 20.0 mts IFO 380 cst, all incl. A/E, no MGO at sea
<b>Port consumption:</b>	Idle about 2.3 mts IFO 380 cst
<b>Winches working:</b>	About 3.0 mts IFO 380 cst (Note: Local port regulations require the burning of MGO in port, e.g. EU ports)

All about, taken from plan but without guarantee.