



# Fleet

**AUG. BOLTEN**  
Wm. Miller's Nachfolger

## LOUISA BOLTEN

<b>Name:</b>	Louisa Bolten
<b>Built:</b>	2009
<b>Flag:</b>	Marshall Islands
<b>Class:</b>	NKK
<b>Type:</b>	Single-deck double-hull bulk carrier, grabs-fitted
<b>Dwat:</b>	30,800 mts on 9.88 m ssw 29,909 mts on 9.67 m wsw
<b>Tpc:</b>	43.60 m on ssw
<b>L.o.a.:</b>	178.70 m
<b>Beam:</b>	28.00 m
<b>Moulded depth:</b>	14.00 m



**Distance waterline to top of hatch coaming in normal ballasted condition:** Midship about 10.24 m

**Tonnage:** (International): gt/nt 19,972 / 10,530

<b>Hatches:</b>	5
<b>Hatch sizes:</b>	No. 1 16.60 m x 15.00 m No. 2 20.80 m x 21.00 m No. 3 20.80 m x 21.00 m No. 4 20.80 m x 21.00 m No. 5 20.80 m x 21.00 m

**Type of hatch covers:** Electro-hydraulic folding type

Hold:	Sizes:	Length	Breadth (fore/aft)	Height	Grain / Bale (cub.ft)
	<b>No. 1</b>	25.10 m	3.00 / 18.75 m	14.20 m	213,991 / 203,288
	<b>No. 2</b>	25.50 m	20.00 m / 22.40 m	14.20 m	305,058 / 289,801
	<b>No. 3</b>	24.55 m	22.40 m / 22.40 m	14.20 m	320,604 / 304,569
	<b>No. 4</b>	26.35 m	22.40 m / 22.40 m	14.20 m	315,409 / 299,632
	<b>No. 5</b>	25.90 m	21.69 m / 6.40 m	14.20 m	284,738 / 270,498

**Total capacity in cubic feet:** 1,439,800 / 1,403,103

**Gear / Grabs:** 4 x 30 mts / 3 x 10 cbm

**Tanktop strength:** 20 mts / sqm

**Ventilation:** Natural

**Speed/consumption:** Abt 13.50 kn on abt 25.00 mts IFO 380 cst

**Port consumption:** Idle abt 2.90 mts IFO 380 cst / with cranes working abt 5.00 IFO 380 cst (bss 24 hrs)  
(Note: In EU ports and where compulsory vessel to burn MGO only, max. 0.1% sulphur content)

All about, taken from plan but without guarantee.