



# Fleet

**AUG. BOLTEN**  
Wm. Miller's Nachfolger

## ANEMONE

<b>Name:</b>	ANEMONE
<b>Built:</b>	2007 (Cochin Shipyard)
<b>Flag:</b>	Bahamas
<b>Class:</b>	ABS
<b>Type:</b>	single-deck bulk carrier
<b>Dwat:</b>	30,587 mts on 9.82 m ssw 29,701 mts on 9.61 m wsw
<b>Tpc:</b>	43.50 mts on ssw
<b>L.o.a.:</b>	178.73 m
<b>Beam:</b>	28.06 m
<b>Moulded depth:</b>	14.00 m



**Distance waterline to top of hatch coaming in normal ballasted condition:** 10.539 m midships

**Tonnage:** (International): gt/nt 19,918 / 10,477

<b>Hatches:</b>	5
<b>Hatch sizes:</b>	No. 1 16.60 m x 15.00 m
	No. 2 20.80 m x 21.00 m
	No. 3 20.80 m x 21.00 m
	No. 4 20.80 m x 21.00 m
	No. 5 20.80 m x 21.00 m

**Type of hatchcovers:** hydraulic folding type

Hold:	Sizes:	Length	Breadth	Height	Grain / Bale (cub.m)
	<b>No. 1</b>	26.40 m	19.60 m	14.10 m	6,064.29 / 5,768.79
	<b>No. 2</b>	25.60 m	22.40 m	14.50 m	8,665.74 / 8,401.65
	<b>No. 3</b>	27.20 m	22.40 m	14.50 m	9,189.53 / 8,878.74
	<b>No. 4</b>	26.40 m	22.40 m	14.50 m	8,943.94 / 8,654.74
	<b>No. 5</b>	27.20 m	22.40 m	14.10 m	8,110.65 / 7,884.26

**Total capacity in cubic meters:** 40,974.15 / 39,588.18

**Gear:** 4 x 30 mts swl

**Tanktop strength:** 20.0 mts / sqm

**Ventilation:** natural

**Speed/consumption:** laden abt: 14.00 kn on abt 24.50 mts HFO (380 cst) - ndas  
12.00 kn on abt 17.00 mts HFO (380 cst) - ndas (eco / wog)

**Port consumption (24h):** idle abt 2.90 mts HFO / all gear working abt 5 mts HFO

(Note: Local port regulations require the burning of MGO in port, e.g. EU ports)

All about, taken from plan but without guarantee.